



palladio collezione
EST. 2012

SALVATORE 10 DESIGNER COLORS

Thickness	Hide type	Average size
0.9 – 1.1 mm	European Bovine	4.6-5 sqmt (48-55 sqft)

Water and stain repellent already dyed into leather

RESIDENTIAL – CONTRACT – HOSPITALITY

TECHNICAL SPECIFICATIONS

Test	Test method	Measurement unit	Result
Tear strenght-Single edge tear	UNI EN ISO 3377-1	N	➤ = 20
Colour fastness to rubbing dry 50 cycles	UNI EN ISO 11640:1998	Grey scale	➤ = 3
Colour fastness to rubbing wet 20 cycles	UNI EN ISO 11640:1998	Grey scale	➤ = 3
Colour fastness to rubbing perspiration 20 cycles	UNI EN ISO 11640:1998 ISO 11641 pH8	Grey scale	➤ = 2
Flexing endurance dry 50.000 cycles	UNI EN ISO 5402		No damage
Colour fastness to artificial light Exposition energy 16.000 kj/sqm	UNI EN ISO 105 B02 (MET5)	Blue scale	➤ = 2/3
Burning behaviour to cigarette and match flame	BS 5852:1979 BS EN 1021-1-2-:2006		Pass
	CAL TB 170		Pass

The test results are referred only to the sample tested

THE PRODUCT COMPLIES WITH THE **REACH** REGULATION

LEATHER
MADE IN ITALY

www.palladio-collezione.com